Step up to a higher level of quality, performanceand reliability









The intuitive dashboard, one touch button and user-friendly menu for operation settings make SC1500 easy to operate even for beginners



Low noise levels allow for daytime cleaning in sensitive areas such as schools, hospitals, etc.



44 liter tank, allows cleaning up to 75 minutes per tank

Stand-on, push the pedal and start cleaning

SC1500 is an innovative stand-on scrubber dryer providing you with superior efficiency due to unprecedented ease of use, increased performance, high quality and reliability. It is an investment in Nilfisk quality that will pay off year after year.

SC1500 brings ease of use to a whole new level. Just step up and you are ready to go. The intuitive display makes it easy for the operator to handle the machine even for the first time, and the small size and handy steering makes maneuvering easier than ever.

Due to its easy handling, high capacity and silent operation SC1500 is the obvious choice for hospitals and health care facilities, schools, office buildings, restaurants, shops and supermarkets as well as sport centers.

Like all Nilfisk machines, it is built with your needs in mind. Outstanding ergonomics and simple, intuitive controls reduce

fatigue and require a minimum of training. You can do your job

more efficiently and save time and money in the process.

- · Easy handling. Just step up and go.
- · OneTouch scrub ON/OFF switch and two brush pressure settings for securing high cleaning performance.
- · Intuitive dashboard with user-friendly menu for setting parameters for cleaning conditions and floor type.
- · 44 liter tank with electronic controlled water flow allows cleaning up to 75 minutes per tank.
- · Low noise level and a silent mode option, makes it ideal for sound sensitive areas and daytime cleaning.
- · Up to 3.5 hours battery running time and optional on board charger increase productivity, performance and reliability.
- · Environment-friendly and cost saving optional Ecoflex system.



Why walk behind when you can get better productivity getting a ride?



A small footprint and yet 51 cm scrubbing power combine performance with easy maneuvering.



Reliability is also our mantra when it comes to service

A Nilfisk machine functions optimally when cared for by regular service and maintenance visits. Therefore we have created the optimal service solution: three levels of service reflecting different requirements and an optional supply of a substitute machine in critical situations.

Service Solutions Standard – Professional maintenance

Your contract encompasses two yearly maintenance visits and 48 hours response time. Breakdown visits and spare parts are billed separately.

Service Solutions Plus Optimised performance

With the Plus solution you have a firm grip on your maintenance and repair costs while knowing that your performance is never compromised, only optimised.

Service Solutions Premium – Maximised uptime

If uptime is your absolute top priority and key concern, Service Solutions Premium is the best choice. A quarterly maintenance visit is included, and there are no sudden financial surprises.

51 cm cleaning width and two pressure settings (23/30kg) for maximum cleaning performance

44 liter tank ensures long operating times and top productivity

Ecoflex and electronic water flow guarantee reliability and environmentally friendly, flexible and easy cleaning at reduced

Easy removal and cleaning of the squeegee without any tools













- Step up and start cleaning fast and convenient
- User-friendly menu allows easy setting of cleaning parameters
- The innovative dashboard is easy to use and requires minimum training
 - Low center of gravity makes the machine stable and safe and a shock protected brush deck insures high reliability

Technical specifications

Description	Unit	SC1500
Voltage	V	24V
Rated power	W	492
Brush motor	W	380
Drive motor	W	280
Sound pressure level at 1.5m	dB(A)	63.33 (60.8)
Productivity rate theoretical/ actual	m²/h	2438/1707
Scrubbing width	mm	510
Max speed	km/h	Fwd 4.8/Rev. 3.5
Solution/recovery tank	litre	44/46
Brush/pad diameter	mm	510
Brush pressure	kg	23/30
Brush/pad speed	rpm	140
Max running time	h	3.5
Battery compartment size	mm	457x455x274
Length x width x height (w/o squeegee)	cm	123x61x133
Net weight	kg	161
Operating weight	kg	326

Specifications and details are subject to change without prior notice.



Kornmarksvej 1 · DK-2605 Brøndby · Denmark Tel.: +45 43 23 81 00 · Fax: +45 43 43 77 00 mail.com@nilfisk.com www.nilfisk.com

